

In the claims:

Claims 21-23 (cancelled).

24. (Currently Amended) A light beam deflector assembly adapted for use in a fiber optic switching module that includes:

a first and a second group of collimator receptacles which are separated from each other at opposite ends of a free space optical path with each collimator receptacle being respectively adapted for receiving and fixing an end of an optical fiber; and

lenses that are supported within the fiber optic switching module each juxtaposed with the end of one optical fiber fixable in the collimator receptacles, and disposed with respect to the end of that optical fiber so a beam of light emittable from the end passes through the lens to propagate as a quasi-collimated beam within the optical path from the lens toward the second or toward the first group of collimator receptacles;

the light beam deflector assembly being positionable along the optical path between the groups of collimator receptacles so at least one quasi-collimated beam of light propagatable from at least one of the lenses impinges thereon, the light beam deflector assembly comprising:

(a) a substrate (212) and

(b) a plurality of reflective light beam deflectors that are fixed to a surface of said substrate (212) which respectively:

i. are:

(1) associated with one of the lenses;

(2) positioned so the quasi-collimated beam of light propagatable from the associated lens impinges upon one of said light beam deflectors to be reflected therefrom; and

(3) energizable by drive signals supplied to said substrate (212) for orienting the light beam deflectors fixed thereto so the quasi-collimated beam of light propagatable from the associated lens, that reflects off the one of said light beam deflectors, also reflects off another selected light beam deflector that is also:

A. positionable along the optical path between the groups of collimator receptacles;

B. energizable by drive signals supplied to said fiber optic switching module; and

C. associated with one of the lenses;

whereby a pair of light beam deflectors, one light beam deflector of the pair included in the light beam deflector assembly, when selected and oriented by drive signals supplied respectively thereto, establish an optical coupling by which a beam of light propagating through the optical path from the end of one optical fiber fixable in the collimator receptacle either of the first or of the second group is reflectable sequentially off the pair of energized light beam deflectors into a selected one of the optical fibers fixable at the second or at the first group of collimator receptacles;

wherein the substrate (212) is formed from an electrically insulating material;

wherein said substrate (212) has electrically conductive electrodes formed on the surface to which said light beam deflectors are fixed, and wherein the drive signals supplied to said substrate (212) generate an electrostatic force between said electrodes and said light beam deflector to energize orientation of said light beam deflectors fixed to said substrate (212);

~~The light beam deflector assembly of claim 23~~ wherein areas on said electrodes of possible contact with said light beam deflectors are at least partially overcoated with electrically insulating material.

25. (Currently Amended) A light beam deflector assembly adapted for use in a fiber optic switching module that includes:

a first and a second group of collimator receptacles which are separated from each other at opposite ends of a free space optical path with each collimator receptacle being respectively adapted for receiving and fixing an end of an optical fiber; and lenses that are supported within the fiber optic switching module each juxtaposed with the end of one optical fiber fixable in the collimator receptacles, and disposed with respect to the end of that optical fiber so a beam of light emittable from the end passes through the lens to propagate as a quasi-collimated beam

within the optical path from the lens toward the second or toward the first group of collimator receptacles;

the light beam deflector assembly being positionable along the optical path between the groups of collimator receptacles so at least one quasi-collimated beam of light propagatable from at least one of the lenses impinges thereon, the light beam deflector assembly comprising:

(a) a substrate (212) and

(b) a plurality of reflective light beam deflectors that are fixed to a surface of said substrate (212) which respectively:

i. are:

(1) associated with one of the lenses;

(2) positioned so the quasi-collimated beam of light propagatable from the associated lens impinges upon one of said light beam deflectors to be reflected therefrom; and

(3) energizable by drive signals supplied to said substrate (212) for orienting the light beam deflectors fixed thereto so the quasi-collimated beam of light propagatable from the associated lens, that reflects off the one of said light beam deflectors, also reflects off another selected light beam deflector that is also:

A. positionable along the optical path between the groups of collimator receptacles;

B. energizable by drive signals supplied to said fiber optic switching module; and

C. associated with one of the lenses;

whereby a pair of light beam deflectors, one light beam deflector of the pair included in the light beam deflector assembly, when selected and oriented by drive signals supplied respectively thereto, establish an optical coupling by which a beam of light propagating through the optical path from the end of one optical fiber fixable in the collimator receptacle either of the first or of the second group is reflectable sequentially off the pair of energized light beam

deflectors into a selected one of the optical fibers fixable at the second or at the first group of collimator receptacles;

wherein the substrate (212) is formed from an electrically insulating material;

wherein said substrate (212) has electrically conductive electrodes formed on the surface to which said light beam deflectors are fixed, and wherein the drive signals supplied to said substrate (212) generate an electrostatic force between said electrodes and said light beam deflector to energize orientation of said light beam deflectors fixed to said substrate (212);

The light beam deflector assembly of claim 23 wherein areas on said electrodes of possible contact with said light beam deflectors are pierced by holes.

Claims 26-30 (cancelled).

31. (Currently Amended) A light beam deflector assembly adapted for use in a fiber optic switching module that includes:

a first and a second group of collimator receptacles which are separated from each other at opposite ends of a free space optical path with each collimator receptacle being respectively adapted for receiving and fixing an end of an optical fiber; and lenses that are supported within the fiber optic switching module each juxtaposed with the end of one optical fiber fixable in the collimator receptacles, and disposed with respect to the end of that optical fiber so a beam of light emittable from the end passes through the lens to propagate as a quasi-collimated beam within the optical path from the lens toward the second or toward the first group of collimator receptacles;

the light beam deflector assembly being positionable along the optical path between the groups of collimator receptacles so at least one quasi-collimated beam of light propagatable from at least one of the lenses impinges thereon, the light beam deflector assembly comprising:

(a) a substrate (212); and

(b) a plurality of reflective light beam deflectors that are fixed to a surface of said substrate (212) which respectively:

i. are:

(1) associated with one of the lenses;

(2) positioned so the quasi-collimated beam of light propagatable from the associated lens impinges upon one of said light beam deflectors to be reflected therefrom; and

(3) energizable by drive signals supplied to said substrate (212) for orienting the light beam deflectors fixed thereto so the quasi-collimated beam of light propagatable from the associated lens, that reflects off the one of said light beam deflectors, also reflects off another selected light beam deflector that is also:

A. positionable along the optical path between the groups of collimator receptacles;

B. energizable by drive signals supplied to said fiber optic switching module; and

C. associated with one of the lenses;

whereby a pair of light beam deflectors, one light beam deflector of the pair included in the light beam deflector assembly, when selected and oriented by drive signals supplied respectively thereto, establish an optical coupling by which a beam of light propagating through the optical path from the end of one optical fiber fixable in the collimator receptacle either of the first or of the second group is reflectable sequentially off the pair of energized light beam deflectors into a selected one of the optical fibers fixable at the second or at the first group of collimator receptacles;

wherein the substrate (212) is formed from an electrically insulating material;

wherein said light beam deflectors are organized as a group;

~~The light beam deflector assembly of claim 26~~ wherein said substrate (212) is elongated, and wherein each light beam deflector fixed to said substrate (212) is supported by hinges for rotation about an axis that is oriented substantially perpendicular to a longitudinal axis of said elongated substrate (212).

32. (Currently Amended) A light beam deflector assembly adapted for use in a fiber optic switching module that includes:

a first and a second group of collimator receptacles which are separated from each other at opposite ends of a free space optical path with each collimator receptacle being respectively adapted for receiving and fixing an end of an optical fiber; and lenses that are supported within the fiber optic switching module each juxtaposed with the end of one optical fiber fixable in the collimator receptacles, and disposed with respect to the end of that optical fiber so a beam of light emittable from the end passes through the lens to propagate as a quasi-collimated beam within the optical path from the lens toward the second or toward the first group of collimator receptacles; the light beam deflector assembly being positionable along the optical path between the groups of collimator receptacles so at least one quasi-collimated beam of light propagatable from at least one of the lenses impinges thereon, the light beam deflector assembly comprising:

(a) a substrate (212); and

(b) a plurality of reflective light beam deflectors that are fixed to a surface of said substrate (212) which respectively:

i. are:

(1) associated with one of the lenses;

(2) positioned so the quasi-collimated beam of light propagatable from the associated lens impinges upon one of said light beam deflectors to be reflected therefrom; and

(3) energizable by drive signals supplied to said substrate (212) for orienting the light beam deflectors fixed thereto so the quasi-collimated beam of light propagatable from the associated lens, that reflects off the one of said light beam deflectors, also reflects off another selected light beam deflector that is also:

A. positionable along the optical path between the groups of collimator receptacles;

B. energizable by drive signals supplied to said fiber optic switching module; and

C. associated with one of the lenses;

whereby a pair of light beam deflectors, one light beam deflector of the pair included in the light beam deflector assembly, when selected and oriented by drive signals supplied respectively thereto, establish an optical coupling by which a beam of light propagating through the optical path from the end of one optical fiber fixable in the collimator receptacle either of the first or of the second group is reflectable sequentially off the pair of energized light beam deflectors into a selected one of the optical fibers fixable at the second or at the first group of collimator receptacles;

wherein the substrate (212) is formed from an electrically insulating material;

wherein said light beam deflectors are organized as a group;

~~The light beam deflector assembly of claim 26~~ wherein each light beam deflector fixed to said substrate (212) is supported by hinges for rotation about an axis that is oriented at an angle of approximately forty-five degrees (45°) to an axis of the group of light beam deflectors.

Claims 33-36 (cancelled).

37. (Currently Amended) A light beam deflector assembly adapted for use in a fiber optic switching module that includes:

a first and a second group of collimator receptacles which are separated from each other at opposite ends of a free space optical path with each collimator receptacle being respectively adapted for receiving and fixing an end of an optical fiber; and lenses that are supported within the fiber optic switching module each juxtaposed with the end of one optical fiber fixable in the collimator receptacles, and disposed with respect to the end of that optical fiber so a beam of light emittable from the end passes through the lens to propagate as a quasi-collimated beam within the optical path from the lens toward the second or toward the first group of collimator receptacles;

the light beam deflector assembly being positionable along the optical path between the groups of collimator receptacles so at least one quasi-collimated beam of light propagatable from at least one of the lenses impinges thereon, the light beam deflector assembly comprising:

(a) a substrate (212); and

(b) a plurality of reflective light beam deflectors that are fixed to a surface of said substrate (212) which respectively:

i. are:

- (1) associated with one of the lenses;
- (2) positioned so the quasi-collimated beam of light propagatable from the associated lens impinges upon one of said light beam deflectors to be reflected therefrom; and
- (3) energizable by drive signals supplied to said substrate (212) for orienting the light beam deflectors fixed thereto so the quasi-collimated beam of light propagatable from the associated lens, that reflects off the one of said light beam deflectors, also reflects off another selected light beam deflector that is also:
 - A. positionable along the optical path between the groups of collimator receptacles;
 - B. energizable by drive signals supplied to said fiber optic switching module; and
 - C. associated with one of the lenses;

whereby a pair of light beam deflectors, one light beam deflector of the pair included in the light beam deflector assembly, when selected and oriented by drive signals supplied respectively thereto, establish an optical coupling by which a beam of light propagating through the optical path from the end of one optical fiber fixable in the collimator receptacle either of the first or of the second group is reflectable sequentially off the pair of energized light beam deflectors into a selected one of the optical fibers fixable at the second or at the first group of collimator receptacles;

wherein the substrate (212) is formed from an electrically insulating material;

wherein the substrate (212) is fabricated from material selected from a group consisting of silicon, polysilicon, Pyrex glass, aluminum oxide and aluminum nitride;

wherein the substrate (212) has integrated circuits integrated therein or thereon;

~~The light beam deflector assembly of claim 35~~ wherein the integrated circuits include amplifiers that receive s which indicate light beam deflector orientation.

38. (Previously added) The light beam deflector assembly of claim 37 wherein each light beam deflector fixed to said substrate (212) is supported for rotation by hinges which include at least one torsion sensor for sensing light beam deflector orientation, the torsion sensors of said light beam deflectors supplying the electrical signals to at least one amplifier included in the light beam deflector assembly.

Claims 39-46 (cancelled).

47. (Currently Amended) A light beam deflector assembly adapted for use in a fiber optic switching module that includes:

a first and a second group of collimator receptacles which are separated from each other at opposite ends of a free space optical path with each collimator receptacle being respectively adapted for receiving and fixing an end of an optical fiber; and

lenses that are supported within the fiber optic switching module each juxtaposed with the end of one optical fiber fixable in the collimator receptacles, and disposed with respect to the end of that optical fiber so a beam of light emittable from the end passes through the lens to propagate as a quasi-collimated beam within the optical path from the lens toward the second or toward the first group of collimator receptacles;

the light beam deflector assembly being positionable along the optical path between the groups of collimator receptacles so at least one quasi-collimated beam of light propagatable from at least one of the lenses impinges thereon, the light beam deflector assembly comprising:

(a) a substrate (212); and

(b) a plurality of reflective light beam deflectors that are fixed to a surface of said substrate (212) which respectively:

i. are:

(1) associated with one of the lenses;

(2) positioned so the quasi-collimated beam of light propagatable from the associated lens impinges upon one of said light beam deflectors to be reflected therefrom; and

(3) energizable by drive signals supplied to said substrate (212) for orienting the light beam deflectors fixed thereto so the quasi-collimated beam of light propagatable from the associated lens, that reflects off the one of said light beam deflectors, also reflects off another selected light beam deflector that is also:

- A. positionable along the optical path between the groups of collimator receptacles;
- B. energizable by drive signals supplied to said fiber optic switching module; and
- C. associated with one of the lenses;

whereby a pair of light beam deflectors, one light beam deflector of the pair included in the light beam deflector assembly, when selected and oriented by drive signals supplied respectively thereto, establish an optical coupling by which a beam of light propagating through the optical path from the end of one optical fiber fixable in the collimator receptacle either of the first or of the second group is reflectable sequentially off the pair of energized light beam deflectors into a selected one of the optical fibers fixable at the second or at the first group of collimator receptacles;

wherein said light beam deflectors are monolithically fabricated from a single-crystal semiconductor layer of a silicon wafer (162).

wherein light beam deflectors respectively include:

an outer frame;

first torsional hinges that project inwardly from the outer frame;

an inner frame supported by the first torsional hinges for rotation about a first axis;

second torsional hinges that project inwardly from the inner frame; and

a central plate that is supported by the second torsional hinges for rotation about a second axis that is not oriented parallel to the first axis, and that has a reflective mirror surface formed thereon;

~~The light beam deflector assembly of claim 46~~ wherein the central plate of light beam deflectors has a width that exceeds a height of the central plate measured perpendicular to the width thereof.

48. (Previously added) The light beam deflector assembly of claim 47 wherein the width of said light beam deflector equals approximately 1.4 times the height thereof.

49. (Currently Amended) A light beam deflector assembly adapted for use in a fiber optic switching module that includes:

a first and a second group of collimator receptacles which are separated from each other at opposite ends of a free space optical path with each collimator receptacle being respectively adapted for receiving and fixing an end of an optical fiber; and lenses that are supported within the fiber optic switching module each juxtaposed with the end of one optical fiber fixable in the collimator receptacles, and disposed with respect to the end of that optical fiber so a beam of light emittable from the end passes through the lens to propagate as a quasi-collimated beam within the optical path from the lens toward the second or toward the first group of collimator receptacles;

the light beam deflector assembly being positionable along the optical path between the groups of collimator receptacles so at least one quasi-collimated beam of light propagatable from at least one of the lenses impinges thereon, the light beam deflector assembly comprising:

(a) a substrate (212); and

(b) a plurality of reflective light beam deflectors that are fixed to a surface of said substrate (212) which respectively:

i. are:

(1) associated with one of the lenses;

(2) positioned so the quasi-collimated beam of light propagatable from the associated lens impinges upon one of said light beam deflectors to be reflected therefrom; and

(3) energizable by drive signals supplied to said substrate (212) for orienting the light beam deflectors fixed thereto so the quasi-collimated beam of light propagatable from the associated lens, that reflects off the one of said light beam deflectors, also reflects off another selected light beam deflector that is also:

- A. positionable along the optical path between the groups of collimator receptacles;
- B. energizable by drive signals supplied to said fiber optic switching module; and
- C. associated with one of the lenses;

whereby a pair of light beam deflectors, one light beam deflector of the pair included in the light beam deflector assembly, when selected and oriented by drive signals supplied respectively thereto, establish an optical coupling by which a beam of light propagating through the optical path from the end of one optical fiber fixable in the collimator receptacle either of the first or of the second group is reflectable sequentially off the pair of energized light beam deflectors into a selected one of the optical fibers fixable at the second or at the first group of collimator receptacles;

wherein said light beam deflectors are monolithically fabricated from a single-crystal semiconductor layer of a silicon wafer (162);

~~The light beam deflector assembly of claim 40~~ wherein the silicon wafer (162) includes a device layer (166) and a handle layer (168) and said light beam deflectors are formed in the device layer (166) of the silicon wafer (162).

50. (Previously Added) The light beam deflector assembly of claim 49 wherein said light beam deflectors are fixed to the substrate (212) with the device layer (166) of the silicon wafer (162) disposed nearest to the substrate (212), and the handle layer (168) disposed further from the substrate (212).

51. (Previously Added) The light beam deflector assembly of claim 50 wherein the handle layer (168) surrounding each of the light beam deflectors is coated with an anti reflection layer to absorb stray light from the quasi-collimated beam of light impinging thereon.

52. (Previously Added) The light beam deflector assembly of claim 49 wherein hinges which support said light beam deflector for rotation about an axis, that are also formed in the device layer (166) of the silicon wafer (162), are thinner than the device layer (166) of the silicon wafer (162).

53. (Previously Added) The light beam deflector assembly of claim 49 wherein a surface of said light beam deflector upon which the quasi-collimated beam of light does not directly impinge has a cavity formed therein which is surrounded by a reinforcing rim.

54. (Cancelled).

55. (Currently Amended) A light beam deflector assembly adapted for use in a fiber optic switching module that includes:
a first and a second group of collimator receptacles which are separated from each other at opposite ends of a free space optical path with each collimator receptacle being respectively adapted for receiving and fixing an end of an optical fiber; and
lenses that are supported within the fiber optic switching module each juxtaposed with the end of one optical fiber fixable in the collimator receptacles, and disposed with respect to the end of that optical fiber so a beam of light emittable from the end passes through the lens to propagate as a quasi-collimated beam within the optical path from the lens toward the second or toward the first group of collimator receptacles;
the light beam deflector assembly being positionable along the optical path between the groups of collimator receptacles so at least one quasi-collimated beam of light propagatable from at least one of the lenses impinges thereon, the light beam deflector assembly comprising:
(a) a substrate (212) and

(b) a plurality of reflective light beam deflectors that are fixed to a surface of said substrate (212) which respectively:

i. are:

- (1) associated with one of the lenses;
- (2) positioned so the quasi-collimated beam of light propagatable from the associated lens impinges upon one of said light beam deflectors to be reflected therefrom; and
- (3) energizable by drive signals supplied to said substrate (212) for orienting the light beam deflectors fixed thereto so the quasi-collimated beam of light propagatable from the associated lens, that reflects off the one of said light beam deflectors, also reflects off another selected light beam deflector that is also:
 - A. positionable along the optical path between the groups of collimator receptacles;
 - B. energizable by drive signals supplied to said fiber optic switching module; and
 - C. associated with one of the lenses;

whereby a pair of light beam deflectors, one light beam deflector of the pair included in the light beam deflector assembly, when selected and oriented by drive signals supplied respectively thereto, establish an optical coupling by which a beam of light propagating through the optical path from the end of one optical fiber fixable in the collimator receptacle either of the first or of the second group is reflectable sequentially off the pair of energized light beam deflectors into a selected one of the optical fibers fixable at the second or at the first group of collimator receptacles;

the light beam deflector assembly further comprising a plurality of light beam deflector orientation sensors at least one of which is associated respectively with each of said light beam deflectors;

~~The light beam deflector assembly of claim 54~~ wherein each light beam deflector fixed to said substrate (212) is supported for rotation by hinges, and wherein said light beam deflector orientation sensor includes at least one torsion sensor formed in the hinges.

56. (Cancelled).

57. (Currently Amended) A light beam deflector assembly adapted for use in a fiber optic switching module that includes:

a first and a second group of collimator receptacles which are separated from each other at opposite ends of a free space optical path with each collimator receptacle being respectively adapted for receiving and fixing an end of an optical fiber; and lenses that are supported within the fiber optic switching module each juxtaposed with the end of one optical fiber fixable in the collimator receptacles, and disposed with respect to the end of that optical fiber so a beam of light emittable from the end passes through the lens to propagate as a quasi-collimated beam within the optical path from the lens toward the second or toward the first group of collimator receptacles;

the light beam deflector assembly being positionable along the optical path between the groups of collimator receptacles so at least one quasi-collimated beam of light propagatable from at least one of the lenses impinges thereon, the light beam deflector assembly comprising:

(a) a substrate (212); and

(b) a plurality of reflective light beam deflectors that are fixed to a surface of said substrate (212) which respectively:

i. are:

(1) associated with one of the lenses;

(2) positioned so the quasi-collimated beam of light propagatable from the associated lens impinges upon one of said light beam deflectors to be reflected therefrom; and

(3) energizable by drive signals supplied to said substrate (212) for orienting the light beam deflectors fixed thereto so the quasi-collimated beam of light propagatable from the associated lens, that reflects off the one of said light beam deflectors, also reflects off another selected light beam deflector that is also:

A. positionable along the optical path between the groups of collimator receptacles;

B. energizable by drive signals supplied to said fiber optic switching module; and

C. associated with one of the lenses;

whereby a pair of light beam deflectors, one light beam deflector of the pair included in the light beam deflector assembly, when selected and oriented by drive signals supplied respectively thereto, establish an optical coupling by which a beam of light propagating through the optical path from the end of one optical fiber fixable in the collimator receptacle either of the first or of the second group is reflectable sequentially off the pair of energized light beam deflectors into a selected one of the optical fibers fixable at the second or at the first group of collimator receptacles;

wherein the quasi-collimated beam of light impinges obliquely upon the light beam deflector to reflect obliquely therefrom;

~~The light beam deflector assembly of claim 56~~ wherein each light beam deflector has a width in a plane established by the impinging and reflected quasi-collimated beam of light which exceeds a height perpendicular to the plane.

58. (Previously Added) The light beam deflector assembly of claim 57 wherein the width of said light beam deflector equals approximately 1.4 times the height thereof.

Claims 59-60 (cancelled).

61. (Currently Amended) A light beam deflector assembly adapted for use in a fiber optic switching module that includes:

a first and a second group of collimator receptacles which are separated from each other at opposite ends of a free space optical path with each collimator receptacle being respectively adapted for receiving and fixing an end of an optical fiber; and lenses that are supported within the fiber optic switching module each juxtaposed with the end of one optical fiber fixable in the collimator receptacles, and disposed with respect to the end of that optical fiber so a beam of light emittable from the end passes

through the lens to propagate as a quasi-collimated beam within the optical path from the lens toward the second or toward the first group of collimator receptacles;
the light beam deflector assembly being positionable along the optical path between the groups of collimator receptacles so at least one quasi-collimated beam of light propagatable from at least one of the lenses impinges thereon, the light beam deflector assembly comprising:

- (a) a substrate (212) and
- (b) a plurality of reflective light beam deflectors that are fixed to a surface of said substrate (212) which respectively:
 - i. are:
 - (1) associated with one of the lenses;
 - (2) positioned so the quasi-collimated beam of light propagatable from the associated lens impinges upon one of said light beam deflectors to be reflected therefrom; and
 - (3) energizable by drive signals supplied to said substrate (212) for orienting the light beam deflectors fixed thereto so the quasi-collimated beam of light propagatable from the associated lens, that reflects off the one of said light beam deflectors, also reflects off another selected light beam deflector that is also:

A. positionable along the optical path between the groups of collimator receptacles;

B. energizable by drive signals supplied to said fiber optic switching module; and

C. associated with one of the lenses;

whereby a pair of light beam deflectors, one light beam deflector of the pair included in the light beam deflector assembly, when selected and oriented by drive signals supplied respectively thereto, establish an optical coupling by which a beam of light propagating through the optical path from the end of one optical fiber fixable in the collimator receptacle either of the first or of the second group is reflectable sequentially off the pair of energized light beam deflectors into a selected one of the optical fibers fixable at the second or at the first group of collimator receptacles;

~~The light beam deflector assembly of claim 21~~ wherein a mirror surface is disposed along a surface of said substrate (212) which is distal from the surface thereof to which said light beam deflectors are fixed, the light beam deflector assembly being:

juxtaposable with a second light beam deflector assembly includable in the fiber optic switching module and positionable in the optical path thereof, the second light beam deflector assembly also having a mirror surface disposed along a surface of the substrate (212) of the second light beam deflector assembly; and
configurable with respect to the mirror surface of the second light beam deflector assembly so the quasi-collimated beam of light that impinges upon light beam deflector first impinges on and is reflected from the mirror surface disposed on the adjacent substrate (212) of the second light beam deflector assembly.

Claims 62-64 (cancelled).

65. (Currently Amended) A light beam deflector assembly adapted for use in a fiber optic switching module that includes:

a first and a second group of collimator receptacles which are separated from each other at opposite ends of a free space optical path with each collimator receptacle being respectively adapted for receiving and fixing an end of an optical fiber; and lenses that are supported within the fiber optic switching module each juxtaposed with the end of one optical fiber fixable in the collimator receptacles, and disposed with respect to the end of that optical fiber so a beam of light emittable from the end passes through the lens to propagate as a quasi-collimated beam within the optical path from the lens toward the second or toward the first group of collimator receptacles;
the light beam deflector assembly being positionable along the optical path between the groups of collimator receptacles so at least one quasi-collimated beam of light propagatable from at least one of the lenses impinges thereon, the light beam deflector assembly comprising:

(a) a substrate (212); and

(b) a plurality of reflective light beam deflectors that are fixed to a surface of said substrate (212) which respectively:

i. are:

- (1) associated with one of the lenses;
- (2) positioned so the quasi-collimated beam of light propagatable from the associated lens impinges upon one of said light beam deflectors to be reflected therefrom; and
- (3) energizable by drive signals supplied to said substrate (212) for orienting the light beam deflectors fixed thereto so the quasi-collimated beam of light propagatable from the associated lens, that reflects off the one of said light beam deflectors, also reflects off another selected light beam deflector that is also:

- A. positionable along the optical path between the groups of collimator receptacles;
- B. energizable by drive signals supplied to said fiber optic switching module; and
- C. associated with one of the lenses;

whereby a pair of light beam deflectors, one light beam deflector of the pair included in the light beam deflector assembly, when selected and oriented by drive signals supplied respectively thereto, establish an optical coupling by which a beam of light propagating through the optical path from the end of one optical fiber fixable in the collimator receptacle either of the first or of the second group is reflectable sequentially off the pair of energized light beam deflectors into a selected one of the optical fibers fixable at the second or at the first group of collimator receptacles;

wherein light beam deflectors respectively include:

an outer frame;
first torsional hinges that project inwardly from the outer frame;
an inner frame supported by the first torsional hinges for rotation about a first axis; second torsional hinges that project inwardly from the inner frame; and
a central plate that is supported by the second torsional hinges for rotation about a second axis that is not oriented parallel to the first axis, and that has a reflective mirror surface formed thereon;

Applicant : Neukermans et al.
Serial No. : 09/729,336
Filed : December 1, 2000
Page : 21 of 23

Attorney's Docket No.: 12485-013001 / 13351XR

wherein said light beam deflectors are organized as a group having an axis to which the second axis of light beam deflectors is oriented substantially parallel;

~~The light beam deflector assembly of claim 63~~ wherein the central plate of light beam deflectors has a width perpendicular to the axis of the group of said light beam deflectors that exceeds a height of the central plate parallel to the axis of the group of said light beam deflectors.